

SDP60-30D (60V30A)

| | |
|---|---|
| MODEL | SDP60-30D |
| Output | |
| Output voltage range (V) | 0-60V |
| Output current range (A) | 0-30A |
| FIXED Voltage Current | OPT |
| Rated output power (W) | Max.1800W |
| Voltage regulation characteristics | |
| Line regulation | 0.1% + 1mVp-p |
| Load regulation | 0.1% + 30mVp-p |
| Ripple /noise | 3mVrms |
| Current regulation characteristics | |
| Line regulation | 0.1% + 1mA _{p-p} |
| Load regulation | 0.1% + 5mA _{p-p} |
| Display | |
| Voltage display | Max 99.9V (FND) |
| Current display | Max 99.9A (FND) |
| In constant voltage/ current operation | CV LED on/ CC LED on |
| Environmental request | |
| Operating temperature / humidity range | 0 to 40 °C / 30 to 80 % RH |
| Stocking temperature / humidity range | -20 to 70 °C / 20 to 80 % RH |
| To-GND voltage | ± 250 VDC |
| Cooling Method | Air Cooling Motor |
| Power source | |
| Input voltage | AC 220V 60 Hz |
| Power Consumption | 1500W FUSE : 15A |
| Dimensions / Weight | |
| Dimensions | 450×520×380 (W×H×D)mm |
| Max. Dimensions | 480×540×445 (W×H×D)mm |
| Weight (approx.) | 60 kg |
| Accessories | Test Cord : 1ea / AC Power Cord : 1ea Short Bar : 1ea / 사용설명서 : 1부 |